



TECHNICAL DATA

AUTOMATIC RINSER						
Model	Output (Bott / h)	Injection Time (Sec)	Dripping Time (Sec)	Consumption per spout (g)	Residual Water (g)	Power (kW)
9 Clamp	1000	3.6	12.6	190	1.8	0.75
	1500	2.4	8.4	140	2.3	
	2000	1.8	6.3	110	2.8	
12 Clamp	1500	2.4	12	140	1.8	0.75
	2000	1.8	9	110	2.2	
	2500	1.44	7.2	90	2.35	
16 Clamp	2000	3.2	15.3	180	1.7	0.75
	3000	1.8	10.2	110	2.15	
	4000	1.35	7.65	85	2.3	
20 Clamp	3000	2.4	12.6	140	1.8	1.5
	4000	1.8	9.45	110	2.2	
	5000	1.44	7.56	90	2.3	
24 Clamp	4000	2.7	11.7	150	1.9	1.5
	5000	2.16	9.36	115	2.2	
	6000	1.8	7.8	110	2.3	
30 Clamp	6000	2.4	9.3	140	2.2	1.5
	7000	2	8	110	2.35	
	8000	1.8	6.98	110	2.4	
36 Clamp	8000	2.2	8	110	2.2	1.5
	9000	2	7.2	100	2.3	
	10000	1.8	6.6	95	2.35	
40 Clamp	10000	2.2	8	110	2.2	2.2
	11000	2	7.2	100	2.3	
	12000	1.8	6.6	95	2.35	
48 Clamp	12000	2.2	8	110	2.2	2.2
	14000	2	7.2	100	2.3	
	16000	1.8	6.6	95	2.35	
60 Clamp	16000	2.2	8	110	2.2	3
	18000	2	7.2	100	2.3	
	20000	1.8	6	95	2.35	